CE0137UM -

25

1/:PRIS

09/530343 527 Rec'd PCT/PTO 27 APR 2000

PROVIDING A SERVICE IN A COMMUNICATION SYSTEM

Field of the Invention

The present invention relates to a method of providing a service in a communication system, wherein the service is provided by a content provider to a user. The present invention also relates to an apparatus for providing a service in a communication system, wherein the service is provided by a content provider to a user. The invention is applicable to but not limited to a cellular radio communication system such as the Universal Mobile Telecommunication System (UMTS) currently under standardisation.

Background of the Invention

Diverse information services currently exist. The content of such information services are typically provided by a content provider, and transmitted to end users by means of some communication network. The communication network is often termed an information highway, and can be for example the internet or other electronic communications routes. Some examples of the type of information provided are news bulletins, travel routes, tourist advice, and so on. The content of such information services are often produced and transmitted in multimedia form.

Information highways or networks such as the internet consist of many sublinks connected in a nodal fashion, and the sub-links are formed of different specific types of communications link, for example digital telephone lines, ISDN lines and analogue telephone lines.

One type of communication link that is expected in future to play an increasing role as one link within information highways such as the internet is that provided by cellular radio communication systems, in particular in the case where the user or subscriber station is a mobile one. Presently

: .-2-

CE0137UM ·

5

10

15

20

25

30

established cellular radio communication systems include GSM systems (Global System for Mobile Communications).

The Universal Mobile Telecommunication System (UMTS) currently under standardisation is intended to provide a harmonised standard under which cellular radio communication systems will provide communications links suitable for transmitting a variety of data services such as information services as described above. It is expected that within the framework of developments such as UMTS or the like, cellular radio communication systems will play an increasing role in information highways such as the internet.

Generally speaking, the above described combination of information provision services and cellular radio communications systems along the lines of UMTS creates a broad range of new engineering problems and challenges. Indeed, one of the challenges faced is to envisage what new opportunities arise to provide users with additional facilities in the light of such a combination.

Summary of the Invention

In the light of the above the present inventors have envisaged that the information services to be handled by systems such as UMTS, especially when in multimedia form, will be extremely diverse and each will have very different requirements with respect to communications parameters such as bandwidth, delay, and error rate. Similarly the present inventors have envisaged that different users will have different types of user station with differing capabilities. The present inventors have envisaged that some content providers will be able to offer users, i.e. customers, a choice as to what overall quality they wish to receive the information at, in terms of for example bandwidth, delay, and error rate, as a function of the price the customer wishes to pay.

CE0137UM : .-3-

The present inventors have further envisaged that since for some classes of information, e.g. news bulletins, there could be several sources of the same or similar information, the user could go to alternative content providers who could charge differently. Similarly, the present inventors have envisaged that cellular communication systems such as UMTS will involve respective arrangements of networks and sub-networks other than the simple linear arrangement of present systems such as GSM. In particular some networks will operate as access networks and others as core networks. Furthermore, the present inventors have envisaged that content providers will potentially be able to input their information at more than one input interface location of the respective network or interconnected networks.

The present inventors have also envisaged that within systems such as UMTS there will consequently be many routes to connect desired services.

Depending on the bandwidths available, facilities, transmission distances and so on, the different cellular radio system network operators' costs will vary and hence the price to the user. The present inventors have envisaged therefore that overall there will be many combinations of content provider, networks, communications parameters and hence price.

20

30

5

10

The present invention advantageously implements means for the content provider and end user to take advantage of the characteristics described above and envisaged by the present inventors.

According to one aspect of the present invention, there is provided a method of providing a service in a communication system, wherein the service is provided by a content provider to a user, as claimed in claim 1.

According to another aspect of the invention, there is provided an apparatus for providing a service in a communication system, wherein the service is provided by a content provider to a user, as claimed in claim 13.

CE0137UM -4-

Further aspects of the invention are as claimed in the dependent claims.

The present invention provides the user with communication parameter options, which enable the user to select the level of service required as a function of price. Having made a selection, the user can advantageously be provided with a sample service corresponding to the selection for a limited duration. Additional specific advantages are apparent from the following description and figures.

Brief Description of the Drawings

FIG. 1 is an illustration of a communication system in accordance with the present invention.

FIG. 2 is a schematic illustration of options provided in a preferred embodiment of the present invention.

FIG. 3 is a schematic illustration of a user station including an external device according to an embodiment of the present invention.

Description of a Preferred Embodiment of the Invention

20

25

30

5

10

15

One particular embodiment of the invention is now described by way of example only. FIG. 1 shows a communication system 100 including a user station 110 and a control station 120. In this example, user station 110 is a mobile station and control station 120 consists of a base station system (BSS). A communication link established between BSS 120 and mobile station 110 is achieved by a radio link 130. The geographical area served by BSS 120 constitutes one cell of a cellular radio communication system.

In the present embodiment BSS 120 is connected to a mobile services switching centre (MSC) 140, which in turn is connected to a public switched telephone network (PSTN) 150. In the present embodiment PSTN 150 is connected to an information network 160, which in the present example

CE0137UM -5-

15

20

25

consists of the internet. The present invention is however also applicable to other information networks, including restricted access networks and private networks.

In the present embodiment the content provider will provide an information service to a user via the route consisting of information network 160, PSTN 150, MSC 140, control station 120, radio link 130 and mobile station 110. The information, in multimedia form, is input to the information network via an interface 170. In the present example this interface consists of a modem and the content provider has produced the information content on a computer system.

In other embodiments interface 170 could be coupled directly to PSTN 150 or MSC 140. One scenario in which direct coupling into MSC 140 could occur would be when a particular content provider has a commercial agreement with a particular cellular radio communication network operator having control of or access to MSC 140.

Furthermore it is to be appreciated that the present invention is applicable to other varieties of network configurations and network components, arranged in different hierarchical, access and interconnection formats, in data handling communications systems such as UMTS. As such, the route via which the content provider will provide an information service to a user in other embodiments of the present invention will be chosen by the skilled person according to the particular characteristics of each overall network arrangement, and similarly the location of interface 170 will be chosen according to the particular characteristics of the overall network arrangement and the nature of the network components.

30 Similarly, it is to be appreciated that according to the specific network configuration and hierarchies, alternative system components will be incorporated serving different roles compared to control station 120, MSC 140

CE0137UM -6-

and PSTN 150. For example, networks such as UMTS ones may incorporate a public data network as opposed to a PSTN, and may incorporate a mobile packet switch as opposed to an MSC. Indeed the invention is applicable to any communication network, including overall networks consisting of subnetworks arranged in parallel and/or superimposed hierarchical logical format, in which a content provider is somewhere inputting an information service into the network arrangement and somewhere else in the overall network arrangement is located a user station by which a user is receiving or intending to receive the information service.

10

5

The method of the present embodiment includes the step of providing to the user a plurality of options related to values of at least one communications parameter to be used during the provision of service, for selection therefrom by the user.

15

In the present embodiment four communications parameters are included, namely

- a) bandwidth,
- b) delay,
- 20
- c) error rate, and
- d) communications route.

In the present embodiment each of these communications parameters, shown as items 210, 220, 230 and 240 in FIG. 2, are presented to the user on the display of the mobile station. Each of these communications parameters will have an effect on the quality of the service as perceived by the user. It is to be appreciated that the present invention applies to other embodiments in the form of other communications parameters which will have an effect on the quality of service as perceived by the user.

30

25

In the present embodiment, the user station comprises a mobile telephone 310 comprising means for communicating over a communication link 320 with

5

10

15

20

25

30

an external device 330, as shown in FIG. 3. The external device can in principle be any device not an integral part of the mobile station, but is preferably a computer or an electronic organiser. Alternatively, the external device can be a smartcard, such as the Subscriber Identity Module (SIM) card used in cellular radio communications systems. The communication link 320 is preferably a fixed cable connection with appropriate interfaces built into the mobile station and the external device, but other communication links such as infrared or radio links can be used.

With respect to each of the above mentioned communications parameters a plurality of options related to the values thereof to be used during the provision of service, shown in FIG. 2 as items 212, 214 and 216 for bandwidth, items 222, 224 and 226 for delay, items 232, 234 and 236 for error rate, and items 242, 244 and 246 for communications route, are provided to the user, on the display of the mobile station. The options are presented in the present example to the user in the form of the readily appreciated terminology. In the case of bandwidth, the terms are "slow", "medium" and "fast", corresponding to the values 9.6kB, 200kB and 2Mb respectively. In the case of delay, the terms are "audio", "up to 30 seconds" and "up to 2 hours", where audio corresponds to 50 microseconds. In the case of error rate, the terms are "poor quality", "medium quality" and "high quality", corresponding to the values 10^4 , 10^8 and 10⁻¹² respectively. In the case of communications route, the identity of different available communications networks are provided, in this example network X, network Y and network Z. It will be readily appreciated that presenting the options to the user in terms of everyday terminology provides benefits related to user friendliness, but it is noted that the relevant options could alternatively be presented in the form of the actual numerical values where appropriate, or in terms of both the user friendly terms and the real numerical values. It will also be appreciated that although the present example specifically cites three options for each parameter, in other examples any discrete number from 2 upward would be possible, moreover the number of options can be different for different respective parameters. Yet further, the CE0137UM '-8-

10

15

20

25

plurality of options could be embodied in the form of a continuous range of values which would preferably be presented to the user in the form of slider bars.

The user selects the required options by use of conventional keyboard/screen interface means, for example by directing movement of a cursor by keyboard keys or mouse operation, and clicking, and so on.

In the present embodiment, a further feature can be that the options are provided as a function of price. The way in which the price function will be presented to the user will be chosen according to the particular situation under consideration. In the present example, a total price is provided, as shown at item 210 in FIG. 2. The price displayed initially is that corresponding to default options, the identity of which will be shown on the display by highlighting means. As the user selects particular alternative options, the price will adjust accordingly. How this is achieved is now explained.

In the present embodiment the function of price is determined using price information input by the content provider and/or price information input by one or more further service providers forming a communications route between the content provider and the user. Thus in the present example price information forming part of the overall price function will have been derived from the operator of PSTN 150, and from the operator of the cellular radio communication system comprising MSC 140 and control station 120, and this price information will have been transmitted to the content provider who will have chosen his own prices as a function of bandwidth, error rate etc., in the light of the provided for such options by the respective operators.

One possibility is that the function of price is determined using stored price information data obtained from an earlier provision of service employing the corresponding values of said at least one communications parameter. In

CE0137UM -9-

5

10

15

20

25

30

other words the content provider will have produced price functions based on earlier actual prices that resulted for equivalent choices of options.

An alternative possibility is that the function of price is determined in real-time using currently applicable price information. Under this possibility the above mentioned operators as well as the content provider will each be providing ongoing input of price variables which are called upon as the user selects different options. Such a process is implemented by a pricing structure. Such a structure can be based on a packet billing system, which takes into account the demanded bandwidth, quality and delay, through which a test packet is sent through the network in order to determine the price which is assigned to it.

In the present embodiment, a further feature can be that simulation means are provided by the content provider for use by the user to carry out simulation of the service that would be provided according to an intended selection by the user. The availability of the simulation means is indicated to the user in association with provision of the plurality of options by means of an item on the display of the user station, such as shown as item 260 in FIG.

2. One possibility is that the user can acquire said simulation means via the communication system, in that software forming the simulation means is provided by the content provider for downloading by the user into his mobile station. An alternative would be that software forming the simulation means was pre-loaded onto the user's mobile station, or available for use in the mobile station by some other means.

The user implements use of the simulation means by further use of conventional keyboard/screen interface means, again for example by directing movement of a cursor by keyboard keys or mouse operation, and clicking, and so on.

CE0137UM -10-

5

30

In each case the software forming the simulation means on the present example will run a simulated version of the service to be provided at the corresponding functions selected by the user. This will enable the user to gauge whether his intended selection of options will in fact provide a service of appearance or content sufficient to meet his requirements.

It is noted that other simulation means other than software are possible, such as electronic circuits.

In the present embodiment, a further feature can be that, after selection by 10 the user, a sample service corresponding to the selection is provided to the user for a limited duration. When the user has made a selection of the options, the actual service is provided, but only for a limited duration. Thus a means is provided for the user to gauge whether his intended selection of options will in fact provide a service of appearance or content sufficient to 15 meet his requirements. This would also facilitate advantageous commercial choices for the content provider such as whether the service of limited duration is to be provided free of cost or at reduced cost. Also, the limited duration can consist of either a predetermined period of time or a predetermined cost, or some combination of these or other features that the 20 skilled person would choose according to the particular system requirements. After the limited duration has expired, the user could request service to be continued or alternatively could select a different combination of options.

The above described features of simulation means and sample service may be provided by the content provider in the alternate, or also they could both be provided.

As described above, in the present embodiment, user station 110 consists of a mobile telephone 310 comprising means for communicating over a communication link 320 with an external device 330. However, alternatively, user station can consist of an electronic organiser module/mobile radio

CE0137UM -11-

telephone combination unit, including a display and keyboard. Alternatively, the user station can be in effective mobile form by being constituted of a pci card plugged into a computer and serving as a radio modem. Similarly, a further alternative is a portable computer with a radio built in. Yet another alternative is a mobile telephone unit in which the user actions corresponding to those described earlier above are carried out by voice activation and/or key stroke methods.

The present invention allows the provision of a facility wherein the user can select a maximum price he wishes to pay, and a choice of parameter value options within that price can be presented to the user.

The present invention provides advantages in any applicable communication system, but is however particularly advantageous in network arrangements including cellular radio communication systems, such as UMTS, since the inclusion of a radio link, and the impact of cellular arrangement, means the different values of communications parameters available are particularly marked and are likely to be particularly price sensitive. The present invention is similarly particularly advantageous in any communication systems with "bandwidth on demand" or similar characteristic. Also, in the case of mobile stations, the mobility aspect itself will mean that a given customer may be prepared to pay more or less, or require different level of service, dependent on his location at a particular time.

25 The present invention is also particularly advantageous in situations where large price variations apply to the parameter values but such parameter values are not important for certain applications. One such application would be telemetry where slow data transfer or large delay might not represent much of a problem.

30

5

10

15

20

A further advantage can be provided whereby the content provider can choose end limits, or limitations of allowable combinations, of the values that the

user is permitted to choose. This may be done in order to maintain bottom line levels of quality, for the purposes of maintaining customer perception or expectations.

CE0137UM -13-

CLAIMS

A method of providing a service in a communication system, wherein the
 service is provided by a content provider to a user,
 the method comprising the step of:
 providing to the user a plurality of options related to values of at least one
 communications parameter to be used during the provision of service, for
 selection therefrom by the user.

10

- 2. A method according to claim 1, wherein said at least one communications parameter is related to the quality of service perceived by the user.
- 15 3. A method according to any preceding claim, wherein said service is an information service.
 - 4. A method according to any preceding claim, wherein said communication system is a radio communication system.

20

25

- 5. A method according to any preceding claim, wherein said at least one communications parameter includes at least one from the group of
 - a) bandwidth,
 - b) delay,
 - c) error rate, and
 - d) communications route.
- 6. A method according to any preceding claim, wherein said options are provided as a function of price.

30

7. A method according to claim 6, wherein the function of price is determined using price information input by the content provider and/or price

CE0137UM -14-

5

15

20

25

information input by one or more further service providers forming a communications route between the content provider and the user.

- 8. A method according to claims 6 or 7, wherein the function of price is determined using stored price information data obtained from an earlier provision of service employing the corresponding values of said at least one communications parameter.
- 9. A method according to claims 6 or 7, wherein the function of price is determined in real-time using currently applicable price information.
 - 10. A method according to any preceding claim, wherein simulation means are provided by the content provider for use by the user to carry out simulation of the service that would be provided according to an intended selection by the user.
 - 11. A method according to claim 10, wherein availability of said simulation means is indicated to the user in association with provision of the plurality of options, and said user can acquire said simulation means via the communication system.
 - 12. A method according to any preceding claim wherein, after selection by the user, a sample service corresponding to the selection is provided to the user for a limited duration.
 - 13. An apparatus for providing a service in a communication system, wherein the service is provided by a content provider to a user, the apparatus comprising:
- means for providing to the user a plurality of options related to values of at least one communications parameter to be used during the provision of service, for selection therefrom by the user.

CE0137UM -15-

14. An apparatus according to claim 13, wherein said at least one communications parameter is related to the quality of service perceived by the user.

5

- 15. An apparatus according to claim 13 or 14, wherein said service is an information service.
- 16. An apparatus according to any of claims 13-15, wherein said10 communication system is a radio communication system.
 - 17. An apparatus according to any of claims 13-16, wherein said at least one communications parameter includes at least one from the group of
 - a) bandwidth,

15

25

30

- b) delay,
- c) error rate, and
- d) communications route.
- 18. An apparatus according to any of claims 13-17, wherein said options are provided as a function of price.
 - 19. An apparatus according to claim 18, wherein the function of price is determined using price information input by the content provider and/or price information input by one or more further service providers forming a communications route between the content provider and the user.
 - 20. An apparatus according to claims 18 or 19, wherein the function of price is determined using stored price information data obtained from an earlier provision of service employing the corresponding values of said at least one communications parameter.

5

- 21. An apparatus according to claims 18 or 19, wherein the function of price is determined in real-time using currently applicable price information.
- 22. An apparatus according to any of claims 13-21, wherein simulation means are provided by the content provider for use by the user to carry out simulation of the service that would be provided according to an intended selection by the user.
- 23. An apparatus according to claim 22, wherein availability of said

 10 simulation means is indicated to the user in association with provision of the
 plurality of options, and said user can acquire said simulation means via the
 communication system.
- 24. An apparatus according to any of claims 13-23, wherein, after selection by the user, a sample service corresponding to the selection is provided to the user for a limited duration.
 - 25. A method substantially as hereinbefore described.
- 20 26. An apparatus for providing a service in a communication system, substantially as hereinbefore described and with reference to the accompanying drawing of FIGS. 1, 2 or 3.

PROVIDING A SERVICE IN A COMMUNICATION SYSTEM

Abstract of the Disclosure

(with reference to FIG. 2) 5

10

15

A method of providing a service in a communication system, wherein the service is provided by a content provider to a user. The method comprises the step of providing to the user a plurality of options related to values of at least one communications parameter to be used during the provision of service, for selection therefrom by the user. Possible communications parameters are a) bandwidth, b) delay, c) error rate, and d) communications route. Also described is corresponding apparatus for providing such a service in a communication system. The invention is particularly advantageous in network arrangements including cellular radio communication systems, such as UMTS.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	. sk	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	ТJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
ВJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Кепуа	NL	Netherlands	YU	Yugoslavia
СН	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
Cl	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
СМ	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

mitt



INTERNATIONAL SEARCH REPORT

(PCT Article 18 and Rules 43 and 44)

Applicant's or agent's file reference CE0137UM/PCT		of Transmittal of International Search Report 220) as well as, where applicable, item 5 below.
nternational application No.	International filing date (day/month/year)	(Earliest) Priority Date (day/month/year)
PCT/EP 99/05765	09/08/1999	27/08/1998
ppHcant HOTOROLA LIMITED et al.		
according to Article 18. A copy is being This international Search Report consi		
X tt is also accompanied	by a copy of each prior art document cited in this	s report.
1. Basis of the report		
	the international search was carried out on the ba unless otherwise indicated under this item.	sis of the international application in the
the international searc Authority (Rule 23.1(b)	h was carried out on the basis of a translation of t	the international application furnished to this
was carried out on the basis of	• •	nternational application, the international search
	ational application in written form.	_
	international application in computer readable for	.
	y to this Authority in written form.	
the statement that the	y to this Authority in computer readble form. subsequently fumished written sequence listing d	loes not go beyond the disclosure in the
international applicatio	n as filed has been furnished.	
the statement that the fumished	Information recorded in computer readable form i	s identical to the written sequence listing has be
2. Certain claims were f	ound unsearchable (See Box I).	
3. Unity of invention is	lacking (see Box II).	
4. With regard to the title.	·	
CC.	submitted by the applicant.	
	blished by this Authority to read as follows:	
·		
. With regard to the abstract,		•
X the text is approved as	submitted by the applicant.	
	bilished, according to Rule 38.2(b), by this Authori the date of mailing of this international search rep	
	ublished with the abstract is Figure No.	2
X as suggested by the ap	oplicant.	None of the figures.
because the applicant	falled to suggest a figure.	

INTERNATIONAL SEARCH REPORT

anal Application No PCT/EP 99/05765

A. CLASSIFICATION OF SUBJECT MATTER IPC 7 H04L29/06 H04L12/28

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

 $\begin{array}{ll} \mbox{Minimum documentation searched} & \mbox{(classification system followed by classification symbols)} \\ \mbox{IPC} & 7 & \mbox{H04L} & \mbox{H04Q} \end{array}$


Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

Category °	ENTS CONSIDERED TO BE RELEVANT Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 97 21294 A (AIRONET WIRELESS COMMUNICATION) 12 June 1997 (1997-06-12) abstract	1-5, 13-17
.,	page 1, line 13 -page 4, line 24 page 6, line 24 -page 12, line 32 page 14, line 3 - line 34 claims 1,6,7,12,14-19,21-23	6,18
Y A		7-12, 19-24

X Further documents are listed in the continuation of box C.	X Patent family members are listed in annex.
"A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filling date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art. "&" document member of the same patent family Date of mailing of the international search report
Date of the actual completion of the international search 25 November 1999	02/12/1999
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Authorized officer Vaskimo, K

2





Inter: .nal Application No PCT/EP 99/05765

	ation) DOCUMENTS CONSIDERED TO BE RELEVANT Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
itegory "		
	EP 0 789 471 A (NIPPON TELEGRAPH & TELEPHONE) 13 August 1997 (1997-08-13) column 1, line 6 -column 6, line 2 column 9, line 33 -column 10, line 6 claim 1	1-3,5, 13-15,17
	Craim 1	6,18 4,7-12, 16,19-24
(WO 98 04088 A (WEBTV NETWORKS INC) 29 January 1998 (1998-01-29) abstract page 3 -page 4 page 6 -page 7 page 20	1,3,6, 13,15,18
A	claims 1,4,5,7	2,4,5, 7-12,14, 16,17, 19-24
X	US 5 675 507 A (BOBO II CHARLES R) 7 October 1997 (1997-10-07) abstract	1,3,13, 15
Α	column 1, line 5 -column 5, line 39 column 8, line 1 -column 9, line 37	2,4-6, 10,12, 14, 16-18, 22,24
Y	WO 97 24879 A (TELE COMMUNICATIONS INC) 10 July 1997 (1997-07-10) page 1, line 5 -page 10, line 19	6,18
A	page 27, line 2 - line 17	1-5, 7-10, 12-17, 19-22,24
А	WO 98 11487 A (AUDIBLE INC) 19 March 1998 (1998-03-19) page 1 -page 3 page 9 -page 12	1,10,12, 13,22,24
A	US 5 233 628 A (RAPPAPORT THEODORE S ET AL) 3 August 1993 (1993-08-03) abstract column 1, line 6 -column 3, line 16 column 12, line 30 -column 15, line 51 column 16, line 57 -column 17, line 7 claims 1-3,7	1,10,12, 13,22,24

INTERNATIONAL SEARCH REPORT

Information on patent family members

Interi nal Application No PCT/EP 99/05765

Patent document cited in search report		Publication date		nt family nber(s)	Publication date
WO 9721294	A	12-06-1997	AU AU CA FP	5950124 A 710939 B 1328997 A 2210792 A 0812503 A 0511835 T	07-09-1999 30-09-1999 27-06-1997 12-06-1997 17-12-1997 10-11-1998
EP 0789471	Α	13-08-1997	JP JP CA	9214936 A 10116239 A 2196622 A	15-08-1997 06-05-1998 07-08-1997
WO 9804088	Α	29-01-1998	US AU EP	5862339 A 3667197 A 0920664 A	19-01-1999 10-02-1998 09-06-1999
US 5675507	Α	07-10-1997	CA EP WO US	2232397 A 0870238 A 9634341 A 5870549 A	31-10-1996 14-10-1998 31-10-1996 09-02-1999
WO 9724879	A	10-07-1997	US AU	5826270 A 1293797 A	20-10-1998 28-07-1997
WO 9811487	A	19-03-1998	US AU EP	5926624 A 4343997 A 0934565 A	20-07-1999 02-04-1998 11-08-1999
us 5233628		03-08-1993	NONE		